

CAR WASH DRYING AGENT

Enjuage y Cera Para Auto



DESCRIPTION:

CAR WASH DRYING AGENT is a concentrated liquid drying agent that does not contain any Mineral Seal Oil or other hydrocarbon ingredients. This product will provide superior beading and water break to insure the driest vehicle possible.

WHERE TO USE:

Conveyor: Apply through drying agent arch.
Rollover: Apply through the drying agent cycle.
High-Pressure In-Bay Automatic: Apply through the drying agent or spray wax cycle.
Self-Serve: Apply through the spray wax cycle.

PRECAUTION: AL USARIO: Si usted no lee Ingles, no use este producto, hasta que la etiqueta le haya sido explicada ampliamente.

TO THE USER: If you cannot read English, do not use this product until this label has been fully explained to you.

DIRECTIONS:

Conveyor Drying Agent Arch: Apply to vehicle at a final dilution rate of 250-300 parts water to one part product.

Rollover Drying Agent Cycle: Apply to vehicle at a final dilution rate of 300-350 parts water to one part product.

High-Pressure In-Bay Spray Wax Cycle: Apply to vehicle at a final dilution rate of 300-350 parts water to one part product.

CAUTIONS:

Do not take internally. If ingested, drink large amounts of water and induce vomiting. Follow with more water and consult a physician.

For eye or skin contact, flush area with clear water for 15 minutes.

Keep container sealed when not in use to prevent evaporation loss and contamination. Triple rinse empty container before disposal in an authorized landfill site.

BRODY
CHEMICAL

TOLL FREE: 800.488.2436
www.brodychemical.com