



# ASPHALT RELEASE



**BR****ODY**  
CHEMICAL





## WELCOME TO BRODY CHEMICAL

Brody Chemical began operations in Salt Lake City, Utah in 1975. Since then, the company has grown from a small local company to one that provides superior products and services to over half of the United States. Brody's success is attributed to its commitment to create innovative and highly effective products—manufactured under strict quality control standards, a responsive technical support team, and a professional, well-trained, service-driven sales force. Brody Chemical's comprehensive product line boasts over 600 different formulations of sanitation, institutional, industrial and maintenance chemicals for professional use. Reducing the risks associated with chemical usage and disposal, avoiding depletion of the Earth's natural resources, and enhancing the safety and work environment for clients are core values of Brody Chemical.



# THE ELIMINATOR

Automatic Drive-Thru system  
United States Patent 6,863,223

This system is equipped to apply a diluted mixture of First Choice asphalt release agent at the rate of 1.5gal of diluted material in 12sec, applying an even coating to all surfaces to be protected. Dilutions are as follows: [our system comes equipped with two preset dilution ratios]

Ratio 1 (for polymer and crumb rubber asphalt mix designs/ high ac content) 946ml of First Choice is diluted with 473 lml of water then applied to truck bed.

Ratio 2 (for conventional asphalt mix designs and low polymer (less than 4% ac)) 378ml of First Choice is diluted with 5299ml of water then applied to truck bed.

Ratio calculations are based on 1hp pump running through a single scale drive-thru system set to run 12sec. one application only.

- Saves precious load-out time.
- Eliminates accidents on spray rack.
- Helps eliminate loitering of drivers.
- With adjustable spray times.
- With infrared detection system.
- Will evenly spray First Choice into truck beds, prior to loading hot mix.
- Applies fast even coatings of First Choice in less than 8-10 sec. for tandem and tri-axel trucks and 12-14 sec. on long trailer and live bottom trucks.
- Will run multiple spray locations, one, two and even three scale sprayers from single unit, all at the same time. Others have tried, and yet, many have failed.



- Available with control tower interface to be fully operational from the control tower to operate, Fully-Automatic or Semi-Automatic and offers on/off operation to select who gets sprayed

## REQUIREMENTS:

Power: 120v@11 FLA (minimum power requirements: 115v at motor, 20amp breaker 12ga wire 100' maximum.)  
Water: 1gpm minimum preferred 3-4gpm. System can be equipped to draw from water tank.

\*U.S. Patents Allowed and Issued for No. 1 and the Eliminator.  
Copyright 2007, Compound Technologies, Inc.

Recommendations for the use of our products and all references are based upon tests believed by us to be factual and accurate. However, due to changing federal and state regulations purchaser assumes all responsibility for regulatory compliance. Since the handling and use of our products are under user's conditions and are beyond our control, no warranty, expressed or implied, including but not limited to merchantability or fitness for a particular use is made concerning our products. The user assumes all risk of use or handling whether or not in accordance with any directions or suggestions of the supplier. Seller shall not be liable to purchaser or any other person for loss or damages directly or indirectly arising from the use of our products, from breach of any warranty or from any other cause, the exclusive remedy against the seller being to require replacement or repair of defective goods. If the purchaser does not accept our products on such terms, they are to be returned at once, unopened and/or unused. For professional and industrial use by trained professionals only. Compound Technologies, Inc. disclaims any liability against infringement of any patent by reason of customer's use of any Compound Technologies, Inc. products in combination with other materials or in any process.

COMPOUND TECHNOLOGIES, INC. WILL ENFORCE ANY AND ALL PATENT INFRINGEMENTS including but not limited to any of its products, equipment and technologies, which are either patented or patent pending. Extensive resources and effort have been invested to bring to market and to perfect these products, equipment and technologies. Patent and/or copyright violators will be prosecuted to the maximum extent possible under the law. Please consult with your attorney.

No. 1, MSX and the Eliminator are Trademarks of Compound Technologies, Inc.

# ASPHALT RELEASE SPRAYER

Lafferty Equipment Manufacturing, Inc. Installation & Operation Instructions

## REQUIREMENTS

Chemical Concentrate Static Tank of Water  
Compressed Air \_\_\_\_\_ up to 4 CFM  
Hose \_\_\_\_\_ 1/2" ID x 25'  
Nozzle \_\_\_\_\_ 2520

## OPTIONS

Stainless Steel Hose Rack  
Large \_\_\_\_\_ # 224150

Stainless Steel Jug Racks  
2 1/2 gal. (8 1/2" x 10 1/2") \_\_\_\_\_ # 224210  
5 Gallon (12" x 12") \_\_\_\_\_ # 224215  
5 Gallon Round Locking \_\_\_\_\_ # 224216

Drum & Tote Stick Lengths, Styles & Seal Materials  
Drum Stick, 33" (Viton or EPDM) # 491643 / 491643-E  
Drum Stick, 48" (Viton or EPDM) # 491648 / 491648-E  
Drum Stick, 54" (Viton or EPDM) # 491645 / 491645-E  
Tote Stick, 48" (Viton or EPDM) # 491654 / 491654-E  
Tote Stick, 54" (Viton or EPDM) # 491656 / 491656-E

Poly/Teflon and Kynar/Teflon Air Pumps  
Pump, WR Poly/Teflon, 3/8", 7GPM  
Max \_\_\_\_\_ # 710911  
Pump, WR Kynar/Teflon, 3/8", 7GPM  
Max \_\_\_\_\_ # 710912

Model # 931108WPS · WPS-MM Asphalt Release Sprayer



## WEIGHT & DIMENSIONS

Single Package  
Shipping Weight 30 lbs.  
Shipping Dimensions 26" x 25" x 11"



**WARNING! READ ALL INSTRUCTIONS BEFORE USING EQUIPMENT**



**BE1100-TL**  
Electric asphalt release spray system complete, 120V, 16A, 20' power cord, 30' push button cord, 40' discharge hose, 15' water & chemical hose inlet, pulls from stagnant water and chem. tanks, trigger spray gun w/48" wand, adjustable run timer and lock out timer, adjustable metering manifold for water chemical mix. "Slide Out" proof.




# ASPHALT RELEASE SPRAYER

## OVERVIEW

The WPS-MM Asphalt Release Sprayer is a chemical spray applicator for diluting and projecting asphalt release chemicals on to truck beds or tools to prevent asphalt from sticking. This system features a lockable, stainless steel enclosure and uses a 3/8" Warren Rupp air-operated, double-diaphragm pump to draw chemical concentrate and water from separate static tanks and blend them to create virtually any dilution ratio. The solution is then projected through the discharge hose, trigger gun, wand and fan nozzle.

Item Number: F1-WC-11AP



For proper performance do NOT modify, substitute nozzle, hose diameter or length. Manufacturer assumes no liability for the use or misuse of this unit.

Wear protective clothing, gloves and eye-wear when working with chemicals. Always direct the discharge away from people and electrical devices.

Follow the chemical manufacturer's safe handling instructions.

DO NOT use d-Limonene or other chemicals that are not compatible with the Santoprene diaphragms.

## TO INSTALL (REFER TO DIAGRAM)

1. Mount the unit above chemical and / or water containers.
2. Securely attach the suction tubes to the check valves as shown in the drawing.
3. Place one tube/strainer in the chemical concentrate(s) and the other in a static container of water. (DO NOT use pressurized water!)
4. Attach a compressed airline to the inlet ball valve. DO NOT TURN ON

## How to Set Your Dilution Ratio:

The adjustment knobs allow you to achieve wide range of dilution ratios.

Turn adjustment knobs counterclockwise to increase flow or clockwise to decrease flow.

For a starting place turn the water knob completely clockwise (closed) then turn 2 turns counterclockwise (open). Then turn the chemical knob completely clockwise (closed) then counterclockwise (open) in 1/4 to 1/2 turn increments until required dilution ratios are achieved. If ratios can't be achieved with the chemical knob all the way counterclockwise start turning water knob clockwise to shift more draw to the chemical side.

## TO OPERATE

Always make sure the discharge is pointed in a safe direction before turning inlet valve on. Trigger can be released at any time during operation but should not be left unattended for long periods of time without closing inlet ball valve.

1. Open the inlet ball valve point the wand in a safe direction and pull the trigger on the gun.
2. Final chemical dilution adjustments will now have to be made. Make adjustments to the knobs based on results.
3. If the solution seems to be too weak slowly turn the chemical knob counterclockwise.
4. Continue opening till the solution is strong enough for the application.
5. Once dilution ratio is set, release the trigger gun or begin application.

# ASPHALT RELEASE SPRAYER

**PREVENTIVE MAINTENANCE:** When the unit will be out of service for extended periods, place chemical tube(s) in water and flush the chemical out of the unit to help prevent chemical from drying out and causing build-up. Periodically check and clean chemical strainer and replace if missing.

Problem	Possible Cause / Solution	
	Startup	Maintenance
A) Air pump will not run or pump solution.	1,5	6,11,12
B) Unit will not draw chemical or water.	2,5	7, 8, 9,10,11
C) Using too much chemical	3	
D) Asphalt sticking in truck bed.	4	
E) Pump runs too fast with no output.		7,8,9,10,11

Possible Cause / Solution	
Startup	Maintenance
1. Open air ball valve fully. Adjust air regulator slowly clockwise. Optimum air pressure is at least 60 PSI 90 PSI maximum.	6. Clean or replace. 7. Water or chemical check valve stuck or clogged Clean or replace.
2. Immerse tube or replenish.	8. Chemical or water strainer clogged up 9. Vacuum leak in metering manifold or suction side of the pump Check and tighten the hose clamps connection(s). After unit has been in service the plastic fittings could have "relaxed" and may need tightened too.  NOTE: This is the most common problem when the unit will not draw water or chemical!
3. Turn chemical knob slightly clockwise or water knob counterclockwise.	10. Chemical or water tube stretched out where tube slides over check valves or pin hole/cut in tube sucking air. Cut off end of tube or replace tube, add a hose clamp, do not over tighten. 11. Problem with air pump Refer to air pump instruction manual. Pump suction and discharge manifolds are loose, tighten bolts.
4. Turn chemical knob slightly counterclockwise or water knob clockwise.	12. Use of an oiler in the airline will cause pump to stall. Use only clean, dry air.
5. Straighten the hose.	



# WALL MOUNTED FOAM UNIT



## WALL MOUNTED FOAM UNIT



- Draws and dilutes product at ratios of 1:1 to 16:1
- Regulates incoming water pressure to ensure consistent foam quality
- Quick-change pump
- 32 inch polypropylene wand for extended foam throw All-poly fluid fittings





## ASPHALT RELEASE (SLIDE OUT)

### ORGANIC LUBRICANTS

---

Brody Chemical's Slide Out (Asphalt Release) is a product specifically developed for the asphalt industry. It is a blend of natural, completely biodegradable products that, when combined in a specially designed formula, works. It works extraordinarily well to prevent asphalt or any tar based product from sticking to metal. Slide Out contains no VOC's (volatile organic compounds).

- 100% biodegradable
- Contains no VOCs
- Non-hazardous
- Simple application process
- Heat stable
- Pour point of 35 degrees
- A barrier, not a cleaning product
- One application is sufficient for several loads
- Works extremely well with hot, high oil content or polymerized asphalt

Brody's Slide Out (Asphalt Release) makes the need to manually clean the bed of a truck a thing of the past, thus reducing man-hours and safety issues. Using Brody's Slide Out (Asphalt Release) eliminates diesel fuel usage simply because this release agent really works.

## ASPHALT ROLLER RELEASE ADDITIVE

### HIGHLY CONCENTRATED

---

This product was developed specifically for the asphalt paving industry. It is a blend of 100% active surfactants that is highly concentrated and produces an extremely slippery foam barrier that prevents asphalt from sticking to the steel wheel when added to the water in the roller/compactor tank. It is especially effective in preventing rubberized asphalt from sticking and being picked up by the roller/compactor steel wheel when asphalt is being put down.

## BMF ASPHALT RELEASE AGENT

### ASPHALT RELEASE AGENT

---

This product is specifically developed for the asphalt industry. It is a blend of natural, completely biodegradable products that when combined in a specially designed formula, works extraordinarily well to prevent asphalt or tar product from sticking to metal. This product contains no VOC'S. Use on transportation vehicles such as dump trucks, dump trailers, flow-boys, live bottom trailers, and hopper trailers. This product may be used on paving equipment such as Rubber Tire Rollers, Pavers and Material Transfer Devices such as the Roadtec (MTV-1000C, SB-1500C, SB-2500B, SB2500C), Blaw-Knox MC-330, Cedarrapids, Mat Smoothness Machines (MS-2, MS-3 and MS-4) and CR662RM roadmix machine and the CAT BG-650B Windrow Elevator spreaders.

## CITRA-GEL DEGREASER

### DISSOLVES DRIED ASPHALT

---

Water dilutable, water rinsable D-limonene based multipurpose degreaser. A blend of builders, surfactants and wetting agents with a high concentration of D-limonene. This formula provides an economical solution and quick penetrating action to dissolve and remove oily and greasy soils from ceramic, marble, Concrete, aluminum, metal and other hard surfaces. Removes carbon exhaust, rust proofing overspray, cosmoline and undercoating and dissolves asphalt on contact. Biodegradable and easy to use.

## DRAG SLAT LUBRICANT

### REDUCE MAINTENANCE COST

---

Asphalt companies have been plagued for years by rust and seizure problems with chains, gates, augers and slats. Drag Slat Lubricant lubricates and seals this equipment, preventing rust and corrosion. This product may be sprayed directly onto drag slats, conveyors, chains and all metal equipment. Drag Slat Lubricant is 100% biodegradable, safe for the environment and does an incredible job lubricating and protecting asphalt plant equipment.



### **FIRST CHOICE ASPHALT RELEASE**

NTPEP APPROVED

Specifically developed for the asphalt industry. This product is a blend of natural, completely biodegradable products that when combined in a specially designed formula, works extraordinarily well to prevent asphalt or tar product from sticking to metal. This product contains no VOC'S. Use on transportation vehicles such as dump trucks, dump trailers, flow-boys, live bottom trailers, and hopper trailers. NTPEP approved for both truck beds & equipment.

### **FIRST CHOICE ASPHALT RELEASE PLUS**

NTPEP APPROVED

Specifically developed for the asphalt industry. This product is a blend of natural, completely biodegradable products that when combined in a specially designed formula, works extraordinarily well to prevent asphalt or tar product from sticking to metal. This product contains no VOC'S. Use on transportation vehicles such as dump trucks, dump trailers, flow-boys, live bottom trailers, and hopper trailers. NTPEP approved for both truck beds & equipment.

### **OIL REMEDIATOR**

DEGRADES COMPLEX HYDROCARBON CHAINS

Oil Remediator is suitable for all weights of petroleum hydrocarbons, sites contaminated with solvents and other volatile organic compounds (such as trichloroethane, benzene, toluene, ethylbenzene, xylenes and BTEX) and fuels such as diesel or gasoline. These microbes have a broad spectrum of metabolic pathways and are thereby able to degrade complex hydrocarbon chains.

### **ORANGE SOLVENT**

POWERFUL ASPHALT REMOVER

This multipurpose concentrate instantly emulsifies grease, oils and fats without the use of harsh acids, alkalis or petroleum solvents. Ideal uses for this product include degreasing equipment, trucks, motors and metal surfaces. This product will remove most resins, adhesives, printing inks, decals, rubber tire marks, tar and asphalt and other tough soils usually requiring solvent-based degreasers.

### **TAR ATTACK CITRUS**

NATURAL OIL FORMULATION

A new natural oil formulation that keeps pace with today's safety and environmental regulations. Powerful degreasers and cleaners, coupled with natural oils and citrus extracts are specially blended to out perform the conventional hazardous solvent degreasers. This multi-purpose concentrate instantly emulsifies grease, oils and fats without the use of harsh acids, alkalines or petroleum solvents. The vapors from this product are not considered harmful. This allows for a wide variety of uses indoors as well as out. This is a great alternative to costly orange solvent products.

### **TAR ATTACK PINE**

NATURAL OIL FORMULATION

A new natural oil formulation that keeps pace with today's safety and environmental regulations. Powerful degreasers and cleaners, coupled with natural oils and pine extracts are specially blended to out perform the conventional hazardous solvent degreasers. This multi-purpose concentrate instantly emulsifies grease, oils and fats without the use of harsh acids, alkalines or petroleum solvents. The vapors from this product are not considered harmful. This allows for a wide variety of uses indoors as well as out. This is a great alternative to costly orange solvent products.

### **TAR BARRIER**

ANTI STICKING AGENT

Tar Barrier prevents applied asphalt crack sealers from sticking to passing vehicles and foot traffic. This product also works as an excellent release agent that keeps tar and asphalt from sticking to the beds of trucks.

Please contact your Brody Chemical representative for a demonstration.



## SLIDE OUT (ASPHALT RELEASE) DEMONSTRATION

### INFORMATION:

Truck #: \_\_\_\_\_

Company Name: \_\_\_\_\_

Driver Name: \_\_\_\_\_

Today's Date: \_\_\_\_\_

### RESULTS/CONDITION OF TRUCK:

Load #1: \_\_\_\_\_

Load #2: \_\_\_\_\_

Load #3: \_\_\_\_\_

Load #4: \_\_\_\_\_

Today your truck will be sprayed with Brody Chemical's Slide Out (Asphalt Release), the only true 100% biodegradable, all-natural, release agent. Slide Out is a unique blend of all-natural oils that bond to the metal surfaces and creates a barrier between the asphalt and the truck bed. Because Slide Out is 100% natural, there is no negative impact to the asphalt, the paint on trucks, the environment, or to the drivers...and it really works! Warm, soapy water will remove product from any surface.

After using Slide Out (Asphalt Release), please let us know how you feel the product works by answering these few questions:

- How well did Slide Out (Asphalt Release) work to keep your truck clean?  
 Excellent       Good       Average
- Is Slide Out (Asphalt Release) the best product that you have used?  
 Yes       No      If 'NO' what was: \_\_\_\_\_
- Would you use Slide Out (Asphalt Release) if it were available?  
 Yes       No
- Are you an independent or an employee of the plant?  
 Independent       Employee

*On behalf of your demonstration team at  
Brody Chemical, we want to thank you for the opportunity to perform this  
demonstration for you today.*





## SLIDE OUT (ASPHALT RELEASE) DEMONSTRATION SURVEY FORM

Company Name: \_\_\_\_\_ Date: \_\_\_\_\_

We will be performing a demonstration of Brody Chemical's Slide Out (Asphalt Release) at your location today. Slide Out (Asphalt Release) is an all-natural, 100% biodegradable, non-hazardous release agent. We are extremely confident in Slide Out (Asphalt Release) because we have not only seen it prove itself, but it is also more effective than any other release agent currently on the market.

We greatly appreciate the opportunity to provide this demonstration for you and would like to request that you complete this quick survey to let us know what you think about our product. Please answer honestly, as we use these surveys in evaluating not only the product, but the demonstration process as well.

- What is the most important feature that you look for in a release agent? (check all that apply)
  - Price                       Keeps truck beds clean                       Environmental
  - Personal Safety                       Number of applications required                       Other
- How would you rate the effectiveness of Slide Out (Asphalt Release)?
  - Excellent                       Good                       Average                       Poor
- Would you consider Slide Out (Asphalt Release) to be more effective than other release agents you have used?
  - Yes                       No
- How many loads per application did you get? \_\_\_\_\_
- What type of mix did you haul? \_\_\_\_\_
- What release agent do you currently use? \_\_\_\_\_
- How often does the release agent you currently use need to be applied? Every \_\_\_\_\_ load(s).
- How much of your current release agent is applied per load? (check appropriate amount)
  - No. Approximate gallons:  ½     1     1½     2     2+
- How would you rate the effectiveness of your current release agent?
  - Excellent                       Good                       Fair                       Poor

Name: \_\_\_\_\_ Phone: \_\_\_\_\_ Truck No.: \_\_\_\_\_

Comments: \_\_\_\_\_  
\_\_\_\_\_  
\_\_\_\_\_

**Please fax completed form to: 801.963.2437 or 800.588.2436**



## ABOUT BRODY CHEMICAL

Brody Chemical sells and provides service to over 50,000 customers in a variety of industries including manufacturing, industrial, mining, automotive, institutional, hospitality, trucking, food and beverage, agricultural, and medical. Brody Chemical's sales representatives are trained to offer technical assistance and recommendations in selecting solutions and cleaning processes that best meet the needs of clients.

**BRODY**  
CHEMICAL

NEALIE WHITE  
720-934-9996  
NEALIE@BRODYCHEMICAL.COM